

PRODUCT DATA SHEET





ELG3416 G-FLEX DYNAMAX C5 ROUSTABOUT IMPACT

PRODUCT CODE CUFF COLOUR SIZE ELG341608 Orange 8 9 ELG341609 White ELG341610 Yellow 10 ELG341611 Brown 11



OTHER DYNAMAX CUT RESISTANT GLOVES



G-Flex Dynamax C5 AirTouch Fingerless



G-Flex Dynamax



G-Flex Dynamax C5 Steeler



G-Flex Dynamax C3 T-Touch Lite

G-FLEX DYNAMAX C5 ROUSTABOUT IMPACT

- T-Touch coating over a blue nitrile 3/4 coating which offers an additional layer of protection including fluids, oils and grease.
- Dynamax® C5 13 gauge seamless liner.
- K-Guard® TPR Exoskeleton Top of hand IMPACT protection.
- Highest Cut level 5 protection.
- "Finger Dip" technology gives total ventilation to back of hand.
- Provides highest levels of cut resistance, abrasion and tear resistance.
- Very comfortable with excellent dexterity, sensitivity and tactility.
- Good grip on most surfaces including those with light oil.
- Four sizes with colour coding identification on the cuff of each glove.

CERTIFICATIONS & STANDARDS

These Gloves are certified by SAI Global to AS/NZS 2161.3:2005 and EN388











General Requirements Risk Category Sizing Marking/labelling etc



	-				
4	543				
Abrasion resistance	'				
Blade cut resistance	_				
Tear resistance					
Bueturo registance					

Mechanical Hazards - Performance Levels							
Test	Level 1	Level 2	Level 3	Level 4	Level 5		
A: Abrasion resistance	100	500	2000	8000			
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0		
C: Tear resistance	10	25	50	75	-		
D: Pucture resistance	20	60	100	150	-		

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.









