ELLIOTTS QUALITY SAFETY GEAR

PDS

PRODUCT DATA SHEET







G-FLEX® T-TOUCH LITE

Super Lightweight T-Touch Lite coating to give you the most comfortable fitting glove.

- >>> Dynamax C3 18 Gauge Seamless blue liner.
- >>> Cut level 3 protection.
- >> "Finger Dip" technology providing ventilation to back of hand.
- >>> Provides highest levels of abrasion and tear resistance.
 Performance Results 4342
- >>> Extremely comfortable, with excellent dexterity, sensitivity and tactility.
- >>> Excellent surface grip including those with light oil.
- >>> Five sizes with colour coding identification on the cuff of each glove.

Materials

- Dynamax C3 18 gauge liner
- Elasticated Cuff
- T-Touch Micro Foam Coating

PRODUCT CODE	CUFF COLOUR	SIZE
ELG343007	BLUE	7
ELG343008	ORANGE	8
ELG343009	WHITE	9
ELG343010	YELLOW	10
ELG343011	BROWN	11

OTHER DYNAMAX CUT RESISTANT GLOVES



G-Flex Steeler



G-Flex Dynamax Roustabout IMPACT



G-Flex Dynamax Roustabout



G-Flex Dynamax C5 AIRTouch

CERTIFICATIONS & STANDARDS

These Gloves are certified by SAI Global to AS/NZS 2161.3:2005 and EN388



AS/NZS 2161.3:2005 LN# SMK40139 ♣ SAIGLOBAL





AS/NZS 2161.2 **EN420**



General Requirements Risk Category Sizing Marking/labelling etc





Abrasion resistance
Blade cut resistance
Tear resistance
Pucture resistance

Mechanical mazarus - r emormanice Levels						
Test	Level 1	Level 2	Level 3	Level 4	Level 5	
A: Abrasion resistance	100	500	2000	8000	-	
B: Blade cut resistance	1,2	2,5	5,0	10,0	20,0	
C: Tear resistance	10	25	50	75	-	

Information regarding protection refers to the working surface, i.e the palm of the glove which has been submitted for testing. The overall classification for gloves with two or more non-interconnected layers does not necessarily reflect the performance of the outermost layer. The protection levels indicated are only valid for new gloves.





